

OBJECT CARPET

Geeignete Klebstoffe Welltex® Circular

In principle, the AT Acoustic Tiles are always fixed to prevent them from slipping, so as to guarantee stability as well as the agreed properties. For this purpose, adhesives that can tack long-term are used for laying dimensionally stable tiles with a textile backing. **(Do not use universal tackifier)**

Manufacturer	Tackifier* /
Uzin Utz AG www.uzin.de	Uzin U 2100 / U 2500
Wulff GmbH & Co. KG www.wulff-gmbh.de	HV 9, Fixiergel
Mapei GmbH www.mapei.com	Ultrabond Eco Fix
Ardex GmbH www.ardex.de	Ardex AF 185

* suitable for qualities Welltex® Circular Acoustic

Important:

AT Acoustic Tiles Installation Guidelines Tile Fixation: AT Acoustic Tiles must always be fixed against slipping to ensure durability and the promised properties. For this purpose, permanently tacky adhesives are used for installing dimensionally stable tiles with textile backing. Adhesive Application: The adhesive applied to the surfaces should have a coverage of approximately 120 g/m² and must be completely dry before installation to avoid adhesion. Failure to do so could prevent later removal of the OBJECT CARPET AT Acoustic Tiles. Absorbent Substrates: For absorbent surfaces, priming of the area is required before applying the adhesive. Double-Height Floors: When applying adhesive on raised flooring systems, care must be taken to prevent adhesive from seeping between the raised floor panels. This could make future removal of the panels more difficult. It may be necessary to tape the panel joints with masking tape. Installation on raised flooring systems should be staggered relative to the panels to ensure optimal coverage. Re-adhesion: If the AT Acoustic Tiles are removed and reinstalled, it may be necessary to renew the fixation.

Final Information

The above information, particularly suggestions for processing and using our products, is based on our knowledge and experience. Liability cannot be derived from these guidelines or from any oral advice. We reserve the right to make changes in line with technological advancements.

OBJECT CARPET Technik 07/2024 www.object-carpet.com/verlegung OBJECT CARPET GmbH | Marie-Curie-Straße 3 | 73770 Denkendorf | Fon +49 (0) 711 / 3402-0 | Fax +49 (0) 711 / 3402-155 | www.object-carpet.com www.object-carpet.com