

# OBJECT CARPET

## **Product information AT WEB**

AT WEB - This carpet tile captivates with a woven loop construction in a mottled design, bringing forth an elegant appearance. The choice of color plays a crucial role in the visibility of the tiles as well as the maintenance effort. Lighter shades may increase sensitivity. A particular criterion is the potential visibility of the seam pattern. Installation Information: It is important to select the appropriate laying pattern (e.g., Herringbone) to achieve the desired visual effect.

## **Inspection requirement**

Before laying, check the goods for quantity, colour loss and ensure they are free from defects. Once the installation has started and the delivered goods have been cut, a complaint about obvious defects is excluded.

## **Preparation/storage**

In the case of interim storage, boxes should not be stacked more than 10 high. Once the inspection has been carried out, the AT Acoustic Tiles to be laid should be brought to the relevant rooms and unpacked 24 hours before processing, in order to acclimatise them. The room temperature should be at least

18°C (64 °F) and the relative humidity 65% at most.

AT Acoustic Tiles within a self-contained room unit must be laid in batches and in the same direction, with the exception of certain patterns. The batch number, information on quality and colour are noted on each box. The direction of the stroke is marked with an arrow on the back of the tiles.

## **Substrates to be covered**

Please note in advance that the substrate is prepared according to ATV/DIN 18365 VOB Part C "Floor covering work", the requirements of DIN 18202 (evenness tolerances) and the respective construction recommendations of the material suppliers. The surfaces to be covered must be dry, firm, level, free of dust and free of cracks and separating agents. They must comply with the applicable building standards and regulations while observing the rules of the trade. In preparation of covering the substrate, the humidity should be 2.0 CM-% for cement screeds and 0.5 CM-% for calcium sulphate screeds.

Please completely remove any possible remaining old coatings. The properly and professionally prepared substrates must be pre-treated with suitable pre-coats/primers and then levelled out with a suitable filler at least 2mm thick.

## **Processing temperatures/air conditioning**

The minimum requirements for the indoor climate must be observed before, during and after installation. The room temperature must be at least 18 °C (64 °F) with a relative humidity of maximum 65%. The surface temperature of the substrate to be covered must not fall below 15 °C (59 °F). The goods to be processed must be acclimatised prior to installation.

## **Fitting on Double Floor**

In case the tiles are intended for installation on a double floor, they must be fully fixed. The tile edges must be set back relative to the double-floor panels upon installation. In so doing, you will get the best covering possible - and no dust joints.

## **Chess board**

The tiles are laid offset by 90° with the running direction and the light and shadow play of the pile layer creates a chessboard pattern.

## **Conductive installation**

In IT data centers and rooms with specific requirements, a conductive installation is often required. The AT Acoustic Tiles are equipped with permanently conductive fiber material and can, therefore, be installed exclusively in a conductive manner.

## **Castors for swivel chairs**

Hard chair castors for textile flooring, soft chair castors for non-textile floor coverings. The use of inappropriate castors may result in destruction of the floor covering. Please note that the supplier has no influence on this fact.

## **General remark**

The above information, especially suggestions for the processing and use of our products, are based on our knowledge and experience. Liability can neither be based on this information nor on oral advice. We reserve the right to make changes in line with technical progress.