

■ ■ Installation instruction

■ ■ AT-Allure 1000 Tile

# OBJECT CARPET

## **Laying**

Using a chalk line or laser, determine a laying line starting from the doors of the respective rooms. Please ensure that the edge tiles are at least 15 cm wide. Starting from the door, the laying is carried out on the chalk line parallel to the main wall. From the door line, the Acoustic Tiles then start in a row up to about the middle of the room. The next tiles are laid in a stepped and joint-tight manner to this row of tiles. The incidence of light determines the shade and the visibility of the joints. You need to try out whether the running direction should run towards the window or away from it.

When laying, ensure that the protruding pile edge is not kinked or pinched when the next Acoustic Tiles are inserted, so that there is a closed surface appearance and no nap jams arise. The Acoustic Tiles should be placed together as possible.

Run your finger along the edge transition of the tiles often so that you can ascertain whether the tiles are flush and can intervene in time.

The cut edges of edge tiles must always be laid towards the wall. Transition areas, power supplies, inspection openings and round cuts should additionally be reinforced at the edges to prevent the individual tufts from breaking out.

## **Fitting on Double Floor**

In case the tiles are intended for installation on a double floor, they must be fully fixed. The tile edges must be set back relative to the double-floor panels upon installation. In so doing, you will get the best covering possible - and no dust joints.