

# OBJECT CARPET

## Typical characteristics

Name of article  
Method of production ISO 2424  
Width ISO 3018  
Surface structure ISO 2424  
Colourways  
Pile material ISO 2424  
Primary backing ISO 2424  
Secondary backing ISO 2424  
Overall weight ISO 8543  
Overall thickness ISO 1765  
Pile service weight  
Additional equipment



## SL-Area 700 Acoustic

Tufted  
approx. 50x50 cm  
Loop  
Style  
100% Econyl® by Aquafil  
PES  
Welltex® textile heavy backing  
approx. 3500 g/m<sup>2</sup>  
approx. 5,5 - 6,5 mm  
approx. 670 g/m<sup>2</sup>  
OC Protect

## Application

Wearability EN 1307 commercial use heavy (33)  
Comfort class EN 1307 LC2

## Ecological characteristics

Conformity certificate 1658-CPR-3425  
DOP 1045-124877  
EPD (Environmental Product Declaration)

## Fastness

Light fastness ISO 105-B02 ≥ 5  
Water fastness EN ISO 105 E01 ≥ 4  
Friction fastness EN ISO 105-X12 ≥ 3-4



Release Date 9.4.2019.

OBJECT CARPET GmbH Rechbergstrasse 19 D-73770 Denkendorf  
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com