

OBJECT CARPET

Typical characteristics

Name of article	SL-Fishbone 700 Acoustic
Method of production ISO 2424	Tufted
Width ISO 3018	approx. 50x50 cm
Surface structure ISO 2424	Loop
Colourways	Style
Pile material ISO 2424	100% Econyl® by Aquafil
Primary backing ISO 2424	PES
Secondary backing ISO 2424	Welltex® textile heavy backing
Overall weight ISO 8543	approx. 3500 g/m ²
Overall thickness ISO 1765	approx. 5,5 mm
Pile service weight	approx. 700 g/m ²
Additional equipment	OC Protect



Application

Wearability EN 1307	commercial use heavy (33)
Comfort class EN 1307	LC2

Ecological characteristics

Conformity certificate	1658-CPR-3425
DOP	1045-115344
EPD (Environmental Product Declaration)	

Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4



Release Date 9.4.2019.

OBJECT CARPET GmbH Rechbergstrasse 19 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com