

OBJECT CARPET

Typical characteristics

Name of article

Method of production ISO 2424

Width ISO 3018

Surface structure ISO 2424

Colourways

Pile material ISO 2424

Primary backing ISO 2424

Secondary backing ISO 2424

Overall weight ISO 8543

Overall thickness ISO 1765

Pile service weight

Additional equipment



SL-Punto 800 Acoustic

Tufted

approx. 50x50 cm

Cut

Style

100% PA 6.6 Gespinst

PES

Welltex® textile heavy backing

approx. 3500 g/m²

approx. 7,0 mm

approx. 870 g/m²

OC Protect

Application

Wearability EN 1307

Comfort class EN 1307

commercial use general (32)

LC3

Ecological characteristics

Conformity certificate

DOP

EPD (Environmental Product Declaration)

1658-CPR-3429

1045-115349

Fastness

Light fastness ISO 105-B02

Water fastness EN ISO 105 E01

Friction fastness EN ISO 105-X12

≥ 5

≥ 4

≥ 3-4



Release Date 9.4.2019.

OBJECT CARPET GmbH Rechbergstrasse 19 D-73770 Denkendorf

Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com