

OBJECT CARPET

Typical characteristics

Name of article

Method of production ISO 2424

Width ISO 3018

Surface structure ISO 2424

Colourways

Pile material ISO 2424

Primary backing ISO 2424

Secondary backing ISO 2424

Overall weight ISO 8543

Overall thickness ISO 1765

Pile service weight

Additional equipment



Splendido 1000

Tufted

approx. 400 cm

Loop

Style

100% Polyamid Antron® Brilliance®

PES

Conductive action back

approx. 2400 g/m²

approx. 8,0 mm

approx. 1000 g/m²

OC Protect

Application

Wearability EN 1307

commercial use heavy (33)

Comfort class EN 1307

LC3

Ecological characteristics

Conformity certificate

1658-CPR-3033

DOP

1045-120901

EPD (Environmental Product Declaration)

EPD-GUT-20160118-CCA1-EN

Fastness

Light fastness ISO 105-B02

≥ 5

Water fastness EN ISO 105 E01

≥ 4

Friction fastness EN ISO 105-X12

≥ 3-4



Release Date 9.4.2019.

OBJECT CARPET GmbH Rechbergstrasse 19 D-73770 Denkendorf

Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com