

# OBJECT CARPET

## Typical characteristics

Name of article

Method of production ISO 2424

Width ISO 3018

Surface structure ISO 2424

Colourways

Pile material ISO 2424

Primary backing ISO 2424

Secondary backing ISO 2424

Overall weight ISO 8543

Overall thickness ISO 1765

Pile service weight



## Structures 700

Flat woven

approx. 400 cm

Loop

Mix

100% PA 6.6 Antron®

PA, PES

Conductive action back

approx. 2200 g/m<sup>2</sup>

approx. 4,0 mm

approx. 750 g/m<sup>2</sup>

## Application

Wearability EN 1307

commercial use heavy (33)

Comfort class EN 1307

LC1

## Ecological characteristics

Conformity certificate

2531-CPR-CXA10145

DOP

1045-120160

EPD (Environmental Product Declaration)

EPD-OBJ-20160206-CAC1-EN

## Fastness

Light fastness ISO 105-B02

≥ 5

Water fastness EN ISO 105 E01

≥ 4

Friction fastness EN ISO 105-X12

≥ 3-4



Release Date 9.4.2019.

OBJECT CARPET GmbH Rechbergstrasse 19 D-73770 Denkendorf

Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com