Characteristic features EN 1307

Name of article

Method of production ISO 2424

Width ISO 3018

Surface structure ISO 2424

Colourways

Pile material ISO 2424

Primary backing ISO 2424

Overall weight ISO 8543

Overall thickness ISO 1765

Pile service weight

AT Aarhus

Flat woven

ca. 50x50

Loop

Style

100% PET

PET

ca. 3700 g/m^2

ca. 5,0 mm

ca. 655 g/m^2

Secondary backing ISO 2424

Electrostatic loading ISO 6356

Surface resistivity ISO 10965 ROT

Transparency to heat ISO 8302 Light fastness ISO 105-B02

Water fastness EN ISO 105 E01

Friction fastness EN ISO 105-X12

Stitch rate ISO 1763

Welltex® Acoustic

< 2 KV

 $10^9 \Omega$

 $0.09 \, K^* m^2 / W$

> 5

> 4 > 3-4

ca. $156.000/m^2$































EN 14041 | DOP: 1060-OC-6323-C4 CPR: 0809-CPR-19006323-C4 | NB: 1658

Health-promoting properties AIR



- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers



Health-promoting ACOUSTIC properties



- High acoustic effectiveness as standard
- Improved impact sound insulation +20dB Enhanced room acoustics $+0.2\alpha$
- Hz 125 250 500 1000 2000 4000 0,02 0,07 0,19 0,01 0,28 0,32
- Increased employee concentration and motivation through enhanced well-being



Environmental properties

- 9C9535A2 PRODIS-ID | product po
- Completely recyclable
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- · Easy cleaning with water only

















Product Information

Installation Instructions

