Characteristic features EN 1307

Name of article	**Chicc 900**
Method of production ISO 2424	Tufted
Width ISO 3018	ca. 400
Surface structure ISO 2424	Cut
Colourways	Uni
Pile material ISO 2424	100% PA 6.6
Primary backing ISO 2424	PES
Overall weight ISO 8543	ca. 2100 g/m²
Overall thickness ISO 1765	ca. 5,00 mm
Pile service weight	ca. 900 g/m²
Secondary backing ISO 2424	Conductive action back
Electrostatic loading ISO 6356	< 2 KV
Surface resistivity ISO 10965 ROT	10^9 Ω
Transparency to heat ISO 8302	0,09 K*m² /W
Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4
Stitch rate ISO 1763	ca. 268.700/m²

CE

EN 14041 | DOP: 1060 OC 3379 | NB: 1658

Health-promoting properties AIR

- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers

HEALTH

Health-promoting ACOUSTIC properties

- Improved impact sound insulation +25dB
  Enhanced room acoustics +0.2α_w

Hz	125	250	500	1000	2000	4000
α_s	0,01	0,03	0,08	0,20	0,28	0,32

- Increased employee concentration and motivation through enhanced well-being
- Acoustically effective

Environmental properties

65A828DE
PRODIS-ID | product pass

- Recycled primary backing
- Easy cleaning with water only

Made in Europe (production according to EU standard)

Product Information

The velour with a fine ribbed structure is characterized by deliberately incorporated iridescent shadow formations that reveal a varying fibre level. This unique property gives the carpet a special characteristic and plays a key role in the design.

Installation Instructions

In order to ensure a precise seam cut within the nap alley, the nap alley must first be opened with a pile reamer before making an accurate cut with a seam cutter (e.g. from Mittag).

Data status 17.04.2024. Subject to changes due to technical advancements.

OBJECT CARPET GmbH | Marie-Curie-Strasse 3 | D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 | technicalsupport@object-carpet.com

OBJECT CARPET