Characteristic features EN 1307



Name of article Method of production ISO 2424 Width ISO 3018

Surface structure ISO 2424

Colourways

Pile material ISO 2424

Primary backing ISO 2424

Overall weight ISO 8543 Overall thickness ISO 1765

Pile service weight

Contract 1000

Tufted

ca. 400

Cut

Uni

100% PA 6

PES

ca. 2400 g/m^2

ca. 8.0 mm

ca. 1000 g/m^2

Secondary backing ISO 2424

Electrostatic loading ISO 6356

Surface resistivity ISO 10965 ROT

Transparency to heat ISO 8302 Light fastness ISO 105-B02

Water fastness EN ISO 105 E01

Friction fastness EN ISO 105-X12

Stitch rate ISO 1763

Action back

< 2 KV

 $10^9 \Omega$

 $0.09 \, K^* m^2 / W$

> 5

> 4 > 3-4

ca. $197.500/m^2$

























EN 14041 | DOP: 1060-OC-3379 CPR: 1658-CPR-3379 | NB: 1658







- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers



70 710 3720-1







EAB78ABB

Health-promoting ACOUSTIC properties



- Improved impact sound insulation +26dB Enhanced room acoustics $+0.25\alpha_{yy}$
- 250 500 1000 2000 125 4000 0,15 0,00 0,05 0,25 0,50 0,65
- Increased employee concentration and motivation through enhanced well-being
- Acoustically effective

Environmental properties

- · Recycled primary backing
- · Easy cleaning with water only

Product Information

The cut pile is characterized by deliberately incorporated iridescent shadow formations that reveal a varying fibre level. This unique property gives the carpet a special characteristic and plays a key role in its design.

Installation Instructions

In order to ensure a precise seam cut within the nap alley, the nap alley must first be opened with a pile reamer before making an accurate cut with a seam cutter (e.g. from Mittag).

















Made in Europe (production according to EU standard)

Data status 30.06.2025. Subject to changes due to technical advancements.