Characteristic features EN 1307



Name of article

Method of production ISO 2424

Width ISO 3018

Surface structure ISO 2424

Colourways

Pile material ISO 2424

Primary backing ISO 2424

Overall weight ISO 8543

Overall thickness ISO 1765

Pile service weight

Cord Web

Flat woven

ca. 400

Schlinge

Mix

100 % Polyamid

PES, PP

ca. 2100 g/m^2

ca. 4.5 mm

ca. 600 g/m^2

Secondary backing ISO 2424

Electrostatic loading ISO 6356

Surface resistivity ISO 10965 ROT

Transparency to heat ISO 8302

Light fastness ISO 105-B02 Water fastness EN ISO 105 E01

Friction fastness EN ISO 105-X12

Stitch rate ISO 1763

Action back

< 2 KV $10^9 \Omega$

 $0.09 \, K^* m^2 / W$

> 5

4 > 3-4

ca. $132000/m^2$

















EN 14041 | DOP: 1060-OC-6323-C2 CPR: 0809-CPR-19006323 - C2 | NB: 1658















- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers



Health-promoting ACOUSTIC properties



- Improved impact sound insulation +16dB Enhanced room acoustics +0.15 $\alpha_{\rm w}$
- 250 500 1000 2000 125 4000 0,00 0,00 0,05 0,20 0,15 0,10
- Increased employee concentration and motivation through enhanced well-being
- Acoustically effective





Environmental properties

768907D3

- · Recycled primary backing
- · Easy cleaning with water only





Made in Europe (production according to EU standard)

EPD 😉

Product Information

The weave construction is visually reminiscent of precise craftsmanship. Seam markings on small patterned flatweaves are typical of the fabric. The reason for the occasional zipper effect in the appearance at the seam edges is not due to the design, but to the fabric construction or patterning.

Installation Instructions

The precise seam cut is carried out professionally using a steel ruler and a laying knife with a trapezoidal blade. The use of pile scissors is recommended for processing cut studs to ensure a flawless appearance.

Data status 30.06.2025. Subject to changes due to technical advancements.