


# OBJECT CARPET

## Typical characteristics

|                               |   |
|-------------------------------|---|
| Name of article               | <br><b>AT-Cosmic</b> |
| Method of production ISO 2424 | Getuftet  |
| Width ISO 3018                | approx. 50x50   |
| Surface structure ISO 2424    | Schlinge  |
| Colourways                    | Mix   |
| Pile material ISO 2424        | 100 % Polyamid Antron® by INVISTA   |
| Primary backing ISO 2424      | PES   |
| Secondary backing ISO 2424    | Welltex® Acoustic   |
| Overall weight ISO 8543       | approx. 2200 g/m <sup>2</sup>   |
| Overall thickness ISO 1765    | approx. 8.4 mm  |
| Pile service weight           | approx. 880 g/m <sup>2</sup>  |

## Application

|                       |                           |
|-----------------------|---------------------------|
| Wearability EN 1307   | commercial use heavy (33) |
| Comfort class EN 1307 | LC2                       |

## Ecological characteristics

|   |                          |
|---|--------------------------|
| Conformity certificate                  | 1658-CPR-3497            |
| DOP                                     | 1060 OC 3497             |
| EPD (Environmental Product Declaration) | EPD-GUT-20160118-CCA1-EN |

## Fastness

|                                  |       |
|----------------------------------|-------|
| Light fastness ISO 105-B02       | ≥ 5   |
| Water fastness EN ISO 105 E01    | 4     |
| Friction fastness EN ISO 105-X12 | ≥ 3-4 |



Release Date 4.5.2022.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf  
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com