Characteristic features EN 1307

Method of production ISO 2424 Width ISO 3018 Surface structure ISO 2424 Colourways Pile material ISO 2424 Primary backing ISO 2424 Overall weight ISO 8543 Overall thickness ISO 1765	AT Cryptive Tufted ca. 50x50 Loop Mix 100% Econyl by Aquafil PES ca. 2150 g/m ² ca. 6,7 mm ca. 710 g/m ²	Secondary backing ISO 2424 Electrostatic loading ISO 6356 Surface resistivity ISO 10965 ROT Transparency to heat ISO 8302 Light fastness ISO 105-B02 Water fastness EN ISO 105 E01 Friction fastness EN ISO 105-X12 Stitch rate ISO 1763	Welltex® Acoustic < 2 KV 10 ⁹ Ω 0,09 K*m² /W ≥ 5 ≥ 4 ≥ 3-4 ca. 252.000/m²
	Brest R22	CE EN 14041 DOP: 1060-OC-3497 CPR: 1658-CPR-3497 NB: 1658	
 Health-promoting properties AI Free from PVC and bitumen. Free from formaldehyde. Reduction of fine dust in the breath Free from harmful emissions and compared on the second compared c	hing air. Ddors.	• <u>Hz</u> 125 250 5	ess as standard insulation +29dB

70 710 3720-8

PRODIS-ID | product pass

(1)

Increased employee concentration and motivation through enhanced well-being

Environmental properties

- Completely recyclable
- 100% recycled yarn
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- Easy cleaning with water only



Product Information

AT CRYPTIVE - Our unique two-tone high/low loop presents an individual tile pattern that intentionally deviates from conventional carpet rolls. In lighter color variations, this visual diversity can vary, underscoring the uniqueness of each tile.

Installation Instructions

Please note that the visual diversity when combining the tiles has no impact on the product quality, but rather is a characteristic feature of the tile. By selectively choosing individual tiles, you effortlessly create a harmonious overall image. Perfect craftsmanship and appealing design for creative space arrangement.

Data status 30.06.2025. Subject to changes due to technical advancements.



 \blacksquare