OBJECT CARPET

Typical characteristics

Name of article	**Deal x Feel**
Method of production ISO 2424	Tufted
Width ISO 3018	approx. 400
Surface structure ISO 2424	Loop
Colourways	Mix
Pile material ISO 2424	100% Econyl by Aquafil
Primary backing ISO 2424	PET
Secondary backing ISO 2424	Action back
Overall weight ISO 8543	approx. 1950 g/m^2
Overall thickness ISO 1765	approx. 7.3 mm
Pile service weight	approx. 950 g/m^2

Application

Wearability EN 1307	commercial use heavy (33)
Comfort class EN 1307	LC3

Ecological characteristics

Conformity certificate	1658-CPR-3547
DOP	1060-OC-3547
EPD (Environmental Product Declaration)	EPD-GUT-20160117-CCA1-EN
Prodis-ID	B1702F59

Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4



Release Date 31.7.2026.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com