Characteristic features EN 1307

Name of article	**Deal x Feel**
Method of production ISO 2424	Tufted
Width ISO 3018	ca. 400
Surface structure ISO 2424	Loop
Colourways	Mix
Pile material ISO 2424	100% Econyl by Aquafil
Primary backing ISO 2424	PET
Overall weight ISO 8543	ca. 2300 g/m²
Overall thickness ISO 1765	ca. 7.5 mm
Pile service weight	ca. 950 g/m²
Secondary backing ISO 2424	Conductive action back
Electrostatic loading ISO 6356	<2 KV
Surface resistivity ISO 10965 ROT	10^9 Ω
Transparency to heat ISO 8302	0,09 K*m² /W
Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4
Stitch rate ISO 1763	ca. 109300/m²

EN 14041 | DOP: 1045-127100 | NB: 1658

Health-promoting properties AIR

- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers

HEALTH

Health-promoting ACOUSTIC properties

- Improved impact sound insulation +28dB
  Enhanced room acoustics +0.25α_w

Hz	125	250	500	1000	2000	4000
α_s	0,0	0,07	0,13	0,31	0,52	0,63

- Increased employee concentration and motivation through enhanced well-being
- Acoustically effective

Environmental properties

B1702F59
PRODIS-ID | product pass

- 100% recycled yarn
- Recycled primary backing
- Easy cleaning with water only

Made in Europe (production according to EU standard)

Product Information

"The expressive loop quality creates a lively, melange-like surface appearance. The delayed regeneration behavior of the tufting quality is typical of the product. Indentations in the fibers recover after a short period of use."

Installation Instructions

The seam is cut professionally from above within the nap alley using a seam cutter (e.g. from Mittag).During this work process, it must be ensured that the nap alley is not left during cutting.

Data status 17.04.2024. Subject to changes due to technical advancements.

OBJECT CARPET GmbH | Marie-Curie-Strasse 3 | D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 | technicalsupport@object-carpet.com

OBJECT CARPET