


# OBJECT CARPET

## Typical characteristics

|                               |   |
|-------------------------------|---|
| Name of article               |  <b>Dune 700</b> |
| Method of production ISO 2424 | Tufted  |
| Width ISO 3018                | approx. 400   |
| Surface structure ISO 2424    | Loop  |
| Colourways                    | Style   |
| Pattern repeat                | 101x412   |
| Pile material ISO 2424        | 100% Econyl by Aquafil  |
| Primary backing ISO 2424      | PES   |
| Secondary backing ISO 2424    | Conductive action back  |
| Overall weight ISO 8543       | approx. 2000 g/m <sup>2</sup>   |
| Overall thickness ISO 1765    | approx. 5,5 - 6,5 mm  |
| Pile service weight           | approx. 670 g/m <sup>2</sup>  |

## Application

|                       |                           |
|-----------------------|---------------------------|
| Wearability EN 1307   | commercial use heavy (33) |
| Comfort class EN 1307 | LC2                       |

## Ecological characteristics

|   |                          |
|---|--------------------------|
| Conformity certificate                  | 1658-CPR-3032            |
| DOP                                     | 1045-124867              |
| EPD (Environmental Product Declaration) | EPD-GUT-20160117-CCA1-EN |
| Prodis-ID                               | 0EA27A03                 |

## Fastness

|                                  |       |
|----------------------------------|-------|
| Light fastness ISO 105-B02       | ≥ 5   |
| Water fastness EN ISO 105 E01    | ≥ 4   |
| Friction fastness EN ISO 105-X12 | ≥ 3-4 |



Release Date 14.11.2022.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf  
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com