

## Characteristic features EN 1307

Name of article	<b>AT Dune 700</b>	Secondary backing ISO 2424	Welltex® Acoustic
Method of production ISO 2424	Tufted	Electrostatic loading ISO 6356	< 2 KV
Width ISO 3018	ca. 50x50	Surface resistivity ISO 10965 ROT	10 <sup>9</sup> Ω
Surface structure ISO 2424	Loop	Transparency to heat ISO 8302	0,09 K*m² /W
Colourways	Style	Light fastness ISO 105-B02	≥ 5
Pile material ISO 2424	100% Econyl by Aquafil	Water fastness EN ISO 105 E01	≥ 4
Primary backing ISO 2424	PES	Friction fastness EN ISO 105-X12	≥ 3-4
Overall weight ISO 8543	ca. 2000 g/m²	Stitch rate ISO 1763	ca. 248.900/m²
Overall thickness ISO 1765	ca. 6,0 mm		
Pile service weight	ca. 710 g/m²		



EN 14041 | DOP: 1060-OC-3497  
CPR: 1658-CPR-3497 | NB: 1658

### Health-promoting properties AIR

- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers

HEALTH

70 710 3720-8



### Health-promoting ACOUSTIC properties

- High acoustic effectiveness as standard
- Improved impact sound insulation +29dB
- Enhanced room acoustics +0.25α<sub>w</sub>

Hz	125	250	500	1000	2000	4000
α <sub>s</sub>	0,01	0,05	0,25	0,25	0,25	0,35

- Increased employee concentration and motivation through enhanced well-being



### Environmental properties

O4AECFC2  
PRODISEID | product pass

- Completely recyclable
- 100% recycled yarn
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- Easy cleaning with water only



### Product Information

The AT DUNE tile presents a fascinating two-tone looped structure that creates a charming tile pattern on each individual tile. Each tile is a unique piece with an individual design. Especially in the lighter color variations, the tile pattern stands out wonderfully with subtle shadow effects in the tile joints.

### Installation Instructions

By consciously sorting during installation, you have the opportunity to influence the overall appearance and reduce production-related duplications in the longitudinal seams. Professional installation creates a refreshingly dynamic surface pattern that adds a pleasantly surprising rejuvenation to any environment. Initial use and regular maintenance with a brush vacuum cleaner enhance the appearance, giving it a progressively more distinct radiance.



Made in Europe (production according to EU standard)

Data status 30.06.2025. Subject to changes due to technical advancements.