Characteristic features EN 1307

Name of article	**AT Dune 700**
Method of production ISO 2424	Tufted
Width ISO 3018	ca. 50x50
Surface structure ISO 2424	Loop
Colourways	Style
Pile material ISO 2424	100% Econyl by Aquafil
Primary backing ISO 2424	PES
Overall weight ISO 8543	ca. 2050 g/m²
Overall thickness ISO 1765	ca. 6,0 mm
Pile service weight	ca. 710 g/m²
Secondary backing ISO 2424	Welltex® Acoustic
Electrostatic loading ISO 6356	< 2 KV
Surface resistivity ISO 10965 ROT	10^9 Ω
Transparency to heat ISO 8302	0,09 K*m² /W
Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4
Stitch rate ISO 1763	ca. 248.900/m²

EN 14041 | DOP: 1060 OC 3497 | NB: 1658

Health-promoting properties AIR

- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers

HEALTH

Health-promoting ACOUSTIC properties

- High acoustic effectiveness as standard
- Improved impact sound insulation +29dB
  Enhanced room acoustics +0.25α_w
-

Hz	125	250	500	1000	2000	4000
α_s	0,01	0,05	0,25	0,25	0,25	0,35

- Increased employee concentration and motivation through enhanced well-being

Environmental properties

04AECFC2
PRODIS-ID | product pass

- Completely recyclable
- 100% recycled yarn
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- Easy cleaning with water only

Made in Europe (production according to EU standard)

Product Information

The AT DUNE tile presents a fascinating two-tone looped structure that creates a charming tile pattern on each individual tile. Each tile is a unique piece with an individual design. Especially in the lighter color variations, the tile pattern stands out wonderfully with subtle shadow effects in the tile joints.

Installation Instructions

By consciously sorting during installation, you have the opportunity to influence the overall appearance and reduce production-related duplications in the longitudinal seams. Professional installation creates a refreshingly dynamic surface pattern that adds a pleasantly surprising rejuvenation to any environment. Initial use and regular maintenance with a brush vacuum cleaner enhance the appearance, giving it a progressively more distinct radiance.

Data status 09.10.2024. Subject to changes due to technical advancements.

OBJECT CARPET GmbH | Marie-Curie-Strasse 3 | D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 | technicalsupport@object-carpet.com

OBJECT CARPET