


OBJECT CARPET

Typical characteristics

Name of article	 AT-ECO Solo
Method of production ISO 2424	Getuftet
Width ISO 3018	approx. 50x50
Surface structure ISO 2424	Schlinge
Colourways	Uni
Pile material ISO 2424	100 % Polyamid Econyl by Aquafil
Primary backing ISO 2424	PES
Secondary backing ISO 2424	T-Pure®, Welltex® Acoustic
Overall weight ISO 8543	approx. 2000 g/m ²
Overall thickness ISO 1765	approx. 6 mm
Pile service weight	approx. 700 g/m ²

Application

Wearability EN 1307	commercial use heavy (33)
Comfort class EN 1307	LC2

Ecological characteristics

Conformity certificate	1658-CPR-3497
DOP	1060 OC 3497
EPD (Environmental Product Declaration)	EPD-GUT-20170017-CCA-1-DE
Prodis-ID	38CE20CE

Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	4
Friction fastness EN ISO 105-X12	3-4



Release Date 14.11.2022.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com