

OBJECT CARPET

Typical characteristics

Name of article
Method of production ISO 2424
Width ISO 3018
Surface structure ISO 2424
Colourways
Pile material ISO 2424
Primary backing ISO 2424
Secondary backing ISO 2424
Overall weight ISO 8543
Overall thickness ISO 1765
Pile service weight



Factum

Getuftet
approx. 400
Velours
Mix
100 % Polyamid Econyl by Aquafil
PES
Action back
approx. 1620 g/m²
approx. 7,0 mm
approx. 900 g/m²

Application

Wearability EN 1307 commercial use general (32)
Comfort class EN 1307 LC2

Ecological characteristics

Conformity certificate 1658-CPR-3547
DOP 1060-OC-3547
EPD (Environmental Product Declaration) EPD-GUT-20220346-CBG1-EN
Prodis-ID BD2DD9DE

Fastness

Light fastness ISO 105-B02 ≥ 5
Water fastness EN ISO 105 E01 4
Friction fastness EN ISO 105-X12 ≥ 3-4



Release Date 24.4.2026.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com