Characteristic features EN 1307

Name of article

Method of production ISO

2424

Width ISO 3018 Surface structure ISO 2424

Colourways

Pile material ISO 2424

Primary backing ISO 2424

Overall weight ISO 8543 Overall thickness ISO 1765

Pile service weight

AT Factum

Getuftet

ca. 50x50 **Velours**

Mix

100 % Polyamid Econyl by

Aquafil

PES

ca. 2200 g/m^2 ca. 7,5 mm

ca. 900 g/m^2

Secondary backing ISO 2424

Electrostatic loading ISO 6356

Surface resistivity ISO 10965 ROT Transparency to heat ISO 8302

Light fastness ISO 105-B02

Water fastness EN ISO 105 E01 Friction fastness EN ISO 105-X12

Stitch rate ISO 1763

Welltex® Acoustic

< 2 KV

 $10^9 \Omega$

 $0.09 \, K^* m^2 / W$

> 5

4 > 3-4

ca. $192500/m^2$



















EN 14041 | DOP: 1060 OC 3497 | NB: 1658













Health-promoting properties AIR



- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers



Health-promoting ACOUSTIC properties



- High acoustic effectiveness as standard
- Improved impact sound insulation +30dB Enhanced room acoustics $+0.3\alpha$

•	Hz	125	250	500	1000	2000	4000
	$\alpha_{\scriptscriptstyle S}$	0,01	0,04	0,41	0,23	0,32	0,43

Increased employee concentration and motivation through enhanced well-being





Environmental properties

084E5E8E

- 100% recycling and take-back responsibility by the manufacturer
- 100% recycled yarn
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- · Easy cleaning with water only















Made in Europe (production according to EU standard)

Product Information

AT FACTUM - The carpet presents itself with a velour construction, featuring a shimmering surface of elegant appearance. The choice of color has a decisive impact on the visibility of the tiles as well as the maintenance effort. The lighter the color choice, the more delicate it can be.

Installation Instructions

Great attention is placed on laying the tiles in a harmonious alignment, thus creating a coherent overall image. At the same time, care is taken not to trap the pile - that is, the yarn ends at the seams, in order to preserve both the aesthetic quality and the lasting functionality of the carpet.

Data status 17.04.2024. Subject to changes due to technical advancements.

