


# OBJECT CARPET

## Typical characteristics

Name of article	 <b>Fine 800</b>
Method of production ISO 2424	Tufted
Width ISO 3018	approx. 400 cm
Surface structure ISO 2424	Loop
Colourways	Mix
Pile material ISO 2424	100% Econyl® by Aquafil
Primary backing ISO 2424	PES
Secondary backing ISO 2424	Conductive action back
Overall weight ISO 8543	approx. 2000 g/m <sup>2</sup>
Overall thickness ISO 1765	approx. 7,80 mm
Pile service weight	approx. 800 g/m <sup>2</sup>
Additional equipment	OC Protect

## Application

Wearability EN 1307	commercial use heavy (33)
Comfort class EN 1307	LC3

## Ecological characteristics

Conformity certificate	1658-CPR-3032
DOP	1045-124865
EPD (Environmental Product Declaration)	EPD-GUT-20160117-CCA1-EN

## Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4



Release Date 1.7.2019.

OBJECT CARPET GmbH Rechbergstrasse 19 D-73770 Denkendorf  
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com