


OBJECT CARPET

Typical characteristics

| | |
|-------------------------------|---|
| Name of article |  Forest 700 |
| Method of production ISO 2424 | Getuftet |
| Width ISO 3018 | approx. 400 |
| Surface structure ISO 2424 | Velours |
| Colourways | Style |
| Pattern repeat | 303x412 |
| Pile material ISO 2424 | 100 % Polyamid Antron® |
| Primary backing ISO 2424 | PES |
| Secondary backing ISO 2424 | Conductive action back |
| Overall weight ISO 8543 | approx. 2250 g/m ² |
| Overall thickness ISO 1765 | approx. 5,5 - 6,5 mm |
| Pile service weight | approx. 950 g/m ² |

Application

| | |
|-----------------------|---------------------------|
| Wearability EN 1307 | commercial use heavy (33) |
| Comfort class EN 1307 | LC2 |

Ecological characteristics

| | |
|---|--------------------------|
| Conformity certificate | 1658-CPR-3032 |
| DOP | 1045-124873 |
| EPD (Environmental Product Declaration) | EPD-GUT-20160117-CCA1-EN |
| Prodis-ID | EC3360CD |

Fastness

| | |
|----------------------------------|-------|
| Light fastness ISO 105-B02 | ≥ 5 |
| Water fastness EN ISO 105 E01 | ≥ 4 |
| Friction fastness EN ISO 105-X12 | ≥ 3-4 |



Release Date 29.1.2023.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com