



Name of article	FORUM Glossy Velours	Secondary backing ISO 2424	Welltex® Acoustic Plus
Method of production ISO 2424	Tufted	Electrostatic loading ISO 6356	< 2 KV
Width ISO 3018	ca. 400	Surface resistivity ISO 10965 ROT	10 ⁹ Ω
Surface structure ISO 2424	Cut	Transparency to heat ISO 8302	0,09 K*m ² /W
Colourways	Style	Light fastness ISO 105-B02	≥ 6-7
Pile material ISO 2424	100% PA 6.6	Water fastness EN ISO 105 E01	≥ 5
Primary backing ISO 2424	PES	Friction fastness EN ISO 105-X12	≥ 5
Overall weight ISO 8543	ca. 3000 g/m ²	Stitch rate ISO 1763	ca. 150.000/m ²
Overall thickness ISO 1765	ca. 11,0 mm		
	ca. 1200 g/m ²		



EN 14041 | DOP: 1045-126862 | NB: 1658

Health-promoting properties AIR



- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers

HEALTH



Health-promoting ACOUSTIC properties



- High acoustic effectiveness as standard
- Improved impact sound insulation +30dB
- Enhanced room acoustics +0.35α_w

Hz	125	250	500	1000	2000	4000
α _s	0,03	0,06	0,33	0,30	0,50	0,70

- Increased employee concentration and motivation through enhanced well-being

Environmental properties

AAF488D9

PRODUSID | product pass

- Completely recyclable
- Recycled primary backing
- 100% recycled secondary backing
- Easy cleaning with water only



Product Information

The voluminous velour with a velvety look and glossy effects is characterized by deliberately incorporated iridescent shadows that reveal a varying fibre level. This unique property gives the carpet a special characteristic and is deliberately integrated into the design

Installation Instructions

In order to ensure a precise seam cut within the nap alley, the nap alley must first be opened with a pile reamer before making an accurate cut with a seam cutter (e.g. from Mittag).



Made in Europe (production according to EU standard)

Data status 23.07.2024. Subject to changes due to technical advancements.