

Characteristic features EN 1307



Name of article	AT FORUM Glossy Velours	Secondary backing ISO 2424	Welltex® Circular Acoustic
Method of production ISO 2424	Tufted	Electrostatic loading ISO 6356	< 2 KV
Width ISO 3018	ca. 50x50	Surface resistivity ISO 10965 ROT	10 ⁹ Ω
Surface structure ISO 2424	Cut	Transparency to heat ISO 8302	0,09 K*m ² /W
Colourways	Style	Light fastness ISO 105-B02	≥ 5
Pile material ISO 2424	100% PA 6.6	Water fastness EN ISO 105 E01	≥ 4
Primary backing ISO 2424	PES	Friction fastness EN ISO 105-X12	≥ 3-4
Overall weight ISO 8543	ca. 2130 g/m ²	Stitch rate ISO 1763	ca. 150.000/m ²
Overall thickness ISO 1765	ca. 11,3 mm		
Pile service weight	ca. 1150 g/m ²		



EN 14041 | DOP: 1060 OC 3549 | NB: 1658

Health-promoting properties AIR

- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers



Health-promoting ACOUSTIC properties

- High acoustic effectiveness as standard
- Improved impact sound insulation +28dB
- Enhanced room acoustics +0.3α_w

Hz	125	250	500	1000	2000	4000
α _s	0,00	0,06	0,24	0,51	0,45	0,66


- Increased employee concentration and motivation through enhanced well-being



Environmental properties

PRODIS-ID | product pass

- Completely recyclable
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- Energy-efficient coating technology without the use of gas and water
- The only carpet worldwide that can be 100% recycled into its components (True circular economy)
- Easy cleaning with water only



Product Information

The voluminous velour with a velvety look and glossy effects is characterized by deliberately incorporated iridescent shadows that reveal a varying fibre level. This unique property gives the carpet a special characteristic and is deliberately integrated into the design.

Installation Instructions

The seam is cut from the back of the fabric using a floor layer's knife with a hooked blade along a steel rail. Only the back construction should be severed in the process.



Made in Europe (production according to EU standard)