



Name of article	FORUM Structured Loop	Secondary backing ISO 2424	Welltex Circular® Acoustic
Method of production ISO 2424	Tufted	Electrostatic loading ISO 6356	< 2 KV
Width ISO 3018	ca. 400	Surface resistivity ISO 10965 ROT	10 ⁹ Ω
Surface structure ISO 2424	Loop	Transparency to heat ISO 8302	0,09 K*m² /W
Colourways	Mix	Light fastness ISO 105-B02	≥ 5
Pile material ISO 2424	100% Econyl by Aquafil	Water fastness EN ISO 105 E01	≥ 4
Primary backing ISO 2424	PES	Friction fastness EN ISO 105-X12	≥ 3-4
Overall weight ISO 8543	ca. 1870 g/m²	Stitch rate ISO 1763	ca. 252.000/m²
Overall thickness ISO 1765	ca. 8,1 mm		
Pile service weight	ca. 740 g/m²		



EN 14041 | DOP: 1060-OC-3548
CPR: 1658-CPR-3548 | NB: 1658

Health-promoting properties AIR



- Free from PVC and bitumen.
- Free from latex and fillers.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers

70 710 3720-11



HEALTH



Health-promoting ACOUSTIC properties



- High acoustic effectiveness as standard
- Improved impact sound insulation +31dB
- Enhanced room acoustics +0.3α_w

Hz	125	250	500	1000	2000	4000
α _s	0,00	0,04	0,14	0,58	0,45	0,50

- Increased employee concentration and motivation through enhanced well-being



Environmental properties

PRODIS-ID | product pass

- Completely recyclable
- 100% recycled yarn
- Recycled primary backing
- 100% recycled secondary backing
- Easy cleaning with water only



Product Information

Installation Instructions



Made in Europe (production according to EU standard)

Data status 30.06.2025. Subject to changes due to technical advancements.