Characteristic features EN 1307



Name of article

Loop

Method of production ISO

2424

Width ISO 3018

Surface structure ISO 2424

Colourways

Pile material ISO 2424

Primary backing ISO 2424

Overall weight ISO 8543 Overall thickness ISO 1765

Pile service weight

AT FORUM Structured

Tufted

ca. 48x48

Loop

Style

100% Econyl by Aquafil

PES

ca. 2200 g/m^2 ca. 7,5 - 8,5 mm

ca. 800 g/m^2

Secondary backing ISO 2424

Electrostatic loading ISO 6356

Surface resistivity ISO 10965 ROT Transparency to heat ISO 8302

Light fastness ISO 105-B02 Water fastness EN ISO 105 E01

Friction fastness EN ISO 105-X12

Stitch rate ISO 1763

Welltex® Acoustic Plus

< 2 KV

 $10^9 \Omega$

 $0.09 \, K^* m^2 / W$

> 6

> 5

> 5

ca. $250.000/m^2$





















EN 14041 | DOP: 1060 OC 6323-C5 | NB: 1658

Health-promoting properties AIR



- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers



Health-promoting ACOUSTIC properties



- High acoustic effectiveness as standard
- Improved impact sound insulation +30dB Enhanced room acoustics $+0.3\alpha$

Hz	125	250	500	1000	2000	4000
$\alpha_{\scriptscriptstyle S}$	0,00	0,06	0,36	0,32	0,39	0,46

Increased employee concentration and motivation through enhanced well-being





Environmental properties

CODD59DD

- Completely recyclable
- 100% recycled yarn
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- Easy cleaning with water only

















Product Information

The AT FORUM Structured Loop tile showcases a captivating, multicolored tile pattern that repeats in a large rapport, creating an individual design on each tile. Especially in the lighter color variations, subtle shadow effects emerge in the tile joints, wonderfully accentuating the pattern.

Installation Instructions

Through deliberate sorting during installation, you can positively influence the overall appearance and minimize production duplications in the longitudinal seams. Professional installation generates a refreshingly dynamic surface pattern that adds a pleasant revitalization to any room. Through initial use and regular maintenance with a brush vacuum cleaner, the appearance steadily gains expressiveness.

