## Characteristic features EN 1307

≤10°Ω

°°€3 ≥0,30

Name of article	AT FORUM Structured	Secondary backing ISO 2424	Welltex® Acoustic Plus
	Loop	Electrostatic loading ISO 6356	< 2 KV
Method of production ISO 2424	Tufted	Surface resistivity ISO 10965 ROT	10º Ω
Width ISO 3018	ca. 48x48	Transparency to heat ISO 8302	0,09 K*m² /W
Surface structure ISO 2424	Loop	Light fastness ISO 105-B02	$\geq 6$
Colourways	Style	Water fastness EN ISO 105 E01	$\geq 5$
Pile material ISO 2424	100% Econyl by Aquafil	Friction fastness EN ISO 105-X12	$\geq 5$
Primary backing ISO 2424	PES Stitch rate ISO 1763	Stitch rate ISO 1763	ca. 250.000/m²
Overall weight ISO 8543	ca. 2200 g/m²		
Overall thickness ISO 1765	ca. 7,5 - 8,5 mm		
Pile service weight	ca. 800 g/m <sup>2</sup>		
	<b>X</b> 7	CE	

lealth-promoting properties AIR 🕥		Health-promoting ACOUSTIC properties 🔊
<ul><li>Free from PVC and bitumen.</li><li>Free from formaldehyde.</li><li>Reduction of fine dust in the breathing air.</li></ul>	НЕАІ	<ul> <li>High acoustic effectiveness as standard</li> <li>Improved impact sound insulation +30dB Enhanced room acoustics +0.3α<sub>w</sub></li> </ul>
• Free from harmful emissions and odors.	HEAL	. <u>Hz</u> 125 250 500 1000 2000 400
TVOC limits are immediately met.		α <sub>s</sub> 0,00 0,06 0,36 0,32 0,39 0,40
Environmental properties	CODD59DD PRODISHD   product pass	Product Information
Completely recyclable		The AT FORUM Structured Loop tile showcases a captivating,
<ul> <li>100% recycled yarn</li> <li>Recycled primary backing</li> <li>100% recycled secondary backing</li> <li>Weight reduction of up to 50%</li> </ul>		multicolored tile pattern that repeats in a large rapport, creating an individual design on each tile. Especially in the lighter color variations, subtle shadow effects emerge in the tile joints, wonderfully accentuating the pattern.



Through deliberate sorting during installation, you can

EN 14041 | DOP: 1060 OC 6323-C5 | NB: 1658

positively influence the overall appearance and minimize production duplications in the longitudinal seams. Professional installation generates a refreshingly dynamic surface pattern that adds a pleasant revitalization to any room. Through initial use and regular maintenance with a brush vacuum cleaner, the appearance steadily gains expressiveness.

Data status 23.07.2024. Subject to changes due to technical advancements.

**OBJECT CARPET**