#### Characteristic features EN 1307

Welltex Circular® Acoustic

< 2 KV

Name of article

Method of production ISO

2424

Width ISO 3018

Surface structure ISO 2424

Colourways

Pile material ISO 2424

Primary backing ISO 2424

Overall weight ISO 8543 Overall thickness ISO 1765

Pile service weight

**AT FORUM Structured** Loop

**Tufted** 

ca. 50x50

Loop

Mix

100% Econyl by Aquafil

**PES** 

ca.  $1870 \text{ g/m}^2$ 

ca. 8,1 mm

ca.  $740 \text{ g/m}^2$ 

Secondary backing ISO 2424

Electrostatic loading ISO 6356

Surface resistivity ISO 10965 ROT  $10^9 \Omega$ 

 $0.09 \, K^* m^2 / W$ Transparency to heat ISO 8302

Light fastness ISO 105-B02 > 5 Water fastness EN ISO 105 E01 > 4 Friction fastness EN ISO 105-X12 > 3-4

Stitch rate ISO 1763 ca.  $252.000/m^2$ 





























EN 14041 | DOP: 1060-OC-3549 CPR: 1658-CPR-3549 | NB: 1658

## **Health-promoting properties AIR**



- Free from PVC and bitumen.
- Free from latex and fillers.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers



70 710 3720-12





## **Health-promoting ACOUSTIC properties**



- High acoustic effectiveness as standard
- Improved impact sound insulation +31dB Enhanced room acoustics  $+0.3\alpha$
- 1000 125 250 500 2000 4000 0,04 0,14 0,58 0,45 0,50
- Increased employee concentration and motivation through enhanced well-being

# **Environmental properties**

PRODIS-ID | product pas



- 100% recycled yarn
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- Energy-efficient coating technology without the use of gas
- The only carpet worldwide that can be 100% recycled into its components (True circular economy)
- Easy cleaning with water only





















Made in Europe (production according to EU standard)

### **Product Information**

The AT FORUM Structured Loop tile showcases a captivating, multicolored tile pattern that repeats in a large rapport, creating an individual design on each tile. Especially in the lighter color variations, subtle shadow effects emerge in the tile joints, wonderfully accentuating the pattern.

### **Installation Instructions**

Through deliberate sorting during installation, you can positively influence the overall appearance and minimize production duplications in the longitudinal seams. Professional installation generates a refreshingly dynamic surface pattern that adds a pleasant revitalization to any room. Through initial use and regular maintenance with a brush vacuum cleaner, the appearance steadily gains expressiveness.

Data status 30.06.2025. Subject to changes due to technical advancements.

