

OBJECT CARPET

Typical characteristics

Name of article
Method of production ISO 2424
Width ISO 3018
Surface structure ISO 2424
Colourways
Pile material ISO 2424
Primary backing ISO 2424
Secondary backing ISO 2424
Overall weight ISO 8543
Overall thickness ISO 1765
Pile service weight
Additional equipment



SL-Glory 1500 Acoustic

Tufted
approx. 50x50 cm
Cut
Uni
100% PA 6.6 Antron®
PES
Welltex® textile heavy backing
approx. 3800 g/m²
approx. 9,0 mm
approx. 1500 g/m²
OC Protect

Application

Wearability EN 1307 commercial use general (32)
Comfort class EN 1307 LC5

Ecological characteristics

Conformity certificate 1658-CPR-3429
DOP 1045-120916

Fastness

Light fastness ISO 105-B02 ≥ 5
Water fastness EN ISO 105 E01 ≥ 4
Friction fastness EN ISO 105-X12 ≥ 3-4



Release Date 1.7.2019.

OBJECT CARPET GmbH Rechbergstrasse 19 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com