

Characteristic features EN 1307



Name of article	AT Glory 1500	Secondary backing ISO 2424	Welltex® Acoustic
Method of production ISO 2424	Tufted	Electrostatic loading ISO 6356	< 2 KV
Width ISO 3018	ca. 50x50	Surface resistivity ISO 10965 ROT	10 ⁹ Ω
Surface structure ISO 2424	Cut	Transparency to heat ISO 8302	0,09 K*m ² /W
Colourways	Uni	Light fastness ISO 105-B02	≥ 5
Pile material ISO 2424	100% PA 6.6	Water fastness EN ISO 105 E01	≥ 4
Primary backing ISO 2424	PES	Friction fastness EN ISO 105-X12	≥ 3-4
Overall weight ISO 8543	ca. 2800 g/m ²	Stitch rate ISO 1763	ca. 130.200/m ²
Overall thickness ISO 1765	ca. 9,0 mm		
Pile service weight	ca. 1500 g/m ²		



EN 14041 | DOP: 1060 OC 3497 | NB: 1658

Health-promoting properties AIR

- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers



Health-promoting ACOUSTIC properties

- High acoustic effectiveness as standard
 - Improved impact sound insulation +30dB
 - Enhanced room acoustics +0.3α_w
- | | | | | | | |
|----------------|------|------|------|------|------|------|
| Hz | 125 | 250 | 500 | 1000 | 2000 | 4000 |
| α _s | 0,02 | 0,07 | 0,34 | 0,36 | 0,42 | 0,54 |
- Increased employee concentration and motivation through enhanced well-being



Environmental properties

1C8B5395
PRODISID | product pass

- 100% recycling and take-back responsibility by the manufacturer
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- Easy cleaning with water only



Product Information

AT GLORY - The carpet presents itself with a velour construction, featuring a shimmering surface of elegant appearance. The choice of color has a decisive impact on the visibility of the tiles as well as the maintenance effort. The lighter the color choice, the more delicate it can be.

Installation Instructions

Great attention is placed on laying the tiles in a harmonious alignment, thus creating a coherent overall image. At the same time, care is taken not to trap the pile - that is, the yarn ends - at the seams, in order to preserve both the aesthetic quality and the lasting functionality of the carpet.



Made in Europe (production according to EU standard)