

# OBJECT CARPET

## Typical characteristics

Name of article  
Method of production ISO 2424  
Width ISO 3018  
Surface structure ISO 2424  
Colourways  
Pile material ISO 2424  
Primary backing ISO 2424  
Secondary backing ISO 2424  
Overall weight ISO 8543  
Overall thickness ISO 1765  
Pile service weight



**Gloss**  
Getuftet  
approx. 400  
Schlinge  
Uni  
100 % Polyamid Econyl by Aquafil  
PP  
Conductive action back  
approx. 2100 g/m<sup>2</sup>  
approx. 7,0 mm  
approx. 920 g/m<sup>2</sup>

## Application

Wearability EN 1307 commercial use general (32)  
Comfort class EN 1307 LC3

## Ecological characteristics

Conformity certificate 1658-CPR3023  
DOP 1060 TT 3023  
EPD (Environmental Product Declaration) EPD-GUT-20170018-CCA1-DE  
Prodis-ID 5CACADE2

## Fastness

Light fastness ISO 105-B02 ≥ 5  
Water fastness EN ISO 105 E01 4  
Friction fastness EN ISO 105-X12 ≥ 3-4



Release Date 4.5.2022.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf  
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com