

OBJECT CARPET

Typical characteristics

Name of article
Method of production ISO 2424
Width ISO 3018
Surface structure ISO 2424
Colourways
Pile material ISO 2424
Primary backing ISO 2424
Secondary backing ISO 2424
Overall weight ISO 8543
Overall thickness ISO 1765
Pile service weight



Gloss
Getuftet
approx. 400
Schlinge
Uni
100 % Polyamid Econyl by Aquafil
PP
Conductive action back
approx. 2100 g/m²
approx. 7,0 mm
approx. 920 g/m²

Application

Wearability EN 1307 commercial use general (32)
Comfort class EN 1307 LC3

Ecological characteristics

Conformity certificate 1658-CPR3023
DOP 1060 TT 3023
EPD (Environmental Product Declaration) EPD-GUT-20170018-CCA1-DE
Prodis-ID 5CACADE2

Fastness

Light fastness ISO 105-B02 ≥ 5
Water fastness EN ISO 105 E01 4
Friction fastness EN ISO 105-X12 ≥ 3-4



Release Date 14.11.2022.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com