Characteristic features EN 1307

Name of article	**AT Helsinki**
Method of production ISO 2424	Flat woven
Width ISO 3018	ca. 50x50
Surface structure ISO 2424	Loop
Colourways	Style
Pile material ISO 2424	100% PET
Primary backing ISO 2424	PET
Overall weight ISO 8543	ca. 3700 g/m²
Overall thickness ISO 1765	ca. 5,0 mm
Pile service weight	ca. 655 g/m²

Secondary backing ISO 2424	Welltex® Acoustic
Electrostatic loading ISO 6356	< 2 KV
Surface resistivity ISO 10965 ROT	10^9 Ω
Transparency to heat ISO 8302	0,09 K*m² /W
Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4
Stitch rate ISO 1763	ca. 156.000/m²

EN 14041 | DOP: 1045-123614 | NB: 1658

Health-promoting properties AIR

- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers

HEALTH

Health-promoting ACOUSTIC properties

- High acoustic effectiveness as standard
- Improved impact sound insulation +20dB
  Enhanced room acoustics +0.2α_w
-

Hz	125	250	500	1000	2000	4000
α_s	0,01	0,02	0,07	0,19	0,28	0,32

- Increased employee concentration and motivation through enhanced well-being

Environmental properties

9C9535A2
PRODIS-ID | product pass

- Completely recyclable
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- Easy cleaning with water only

Made in Europe (production according to EU standard)

Product Information

Installation Instructions

Data status 09.10.2024. Subject to changes due to technical advancements.

OBJECT CARPET GmbH | Marie-Curie-Strasse 3 | D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 | technicalsupport@object-carpet.com

OBJECT CARPET