


OBJECT CARPET

Typical characteristics

Name of article	 HIGHS x SIGHS
Method of production ISO 2424	Tufted
Width ISO 3018	approx. 400
Surface structure ISO 2424	Cut
Colourways	Uni
Pile material ISO 2424	100% PA 6.6
Primary backing ISO 2424	PP
Secondary backing ISO 2424	Conductive action back
Overall weight ISO 8543	approx. 2700 g/m ²
Overall thickness ISO 1765	approx. 14 mm
Pile service weight	approx. 2200 g/m ²

Application

Wearability EN 1307	commercial use general (32)
Comfort class EN 1307	LC5

Ecological characteristics

Conformity certificate	2401-CPR-RCN2019/161
DOP	1045-127105
EPD (Environmental Product Declaration)	EPD-GUT-20160118-CCA1-EN

Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4



Release Date 17.9.2020.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com