



Name of article	Highs x Sighs	Secondary backing ISO 2424	Action back
Method of production ISO 2424	Tufted	Electrostatic loading ISO 6356	<2 KV
Width ISO 3018	ca. 400	Surface resistivity ISO 10965 ROT	
Surface structure ISO 2424	Cut	Transparency to heat ISO 8302	0,09 K*m² /W
Colourways	Uni	Light fastness ISO 105-B02	≥ 5
Pile material ISO 2424	100% PET recycelt	Water fastness EN ISO 105 E01	≥ 4
Primary backing ISO 2424	PP	Friction fastness EN ISO 105-X12	≥ 3-4
Overall weight ISO 8543	ca. 3170 g/m²	Stitch rate ISO 1763	ca. 117700/m²
Overall thickness ISO 1765	ca. 15 mm		
Pile service weight	ca. 2200 g/m²		



EN 14041 | DOP: 1060-OC-2024/166-1
CPR: CE-System 3 | NB: 1658

Health-promoting properties AIR

- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers

Health-promoting ACOUSTIC properties

- Improved impact sound insulation +30dB
- Enhanced room acoustics +0.3α_w
- Increased employee concentration and motivation through enhanced well-being
- Acoustically effective

Hz	125	250	500	1000	2000	4000
α _s	0,05	0,09	0,18	0,39	0,61	0,64

Environmental properties

BAD4850D
PRODID-ID | product pass

- 100% recycled yarn
- Recycled primary backing
- Easy cleaning with water only

Product Information

The velour with a high material density is characterized by deliberately incorporated iridescent shadows, which reveal a varying fibre level. This unique property gives the carpet a special characteristic and plays a key role in its design.

Installation Instructions

In order to ensure a precise seam cut within the nap alley, the nap alley must first be opened with a pile reamer before making an accurate cut with a seam cutter (e.g. from Mittag).

Made in Europe (production according to EU standard)