OBJECT CARPET

Typical characteristics

Name of article	**AT-Industrial**
Method of production ISO 2424	Getuftet
Width ISO 3018	approx. 25x100
Surface structure ISO 2424	Velours
Pile material ISO 2424	100 % Polyamid Alto®
Primary backing ISO 2424	PES
Secondary backing ISO 2424	
Overall weight ISO 8543	approx. 4200 g/m^2
Overall thickness ISO 1765	approx. 7.8 mm
Pile service weight	approx. 500 g/m^2

Application

Wearability EN 1307	commercial use heavy (33)
Comfort class EN 1307	LC1

Ecological characteristics

Conformity certificate	1658-CPR-3381
DOP	1060 OC 3381
EPD (Environmental Product Declaration)	EPD-GUT-20160228-CBH1-DE
Prodis-ID	EE014AE7

Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	4
Friction fastness EN ISO 105-X12	≥ 3-4

Release Date 21.4.2024.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com