


OBJECT CARPET

Typical characteristics

Name of article	 Loop 700
Method of production ISO 2424	Woven
Width ISO 3018	approx. 400
Surface structure ISO 2424	Flat woven
Colourways	Mix
Pile material ISO 2424	100 % Polyamid Econyl by Aquafil
Primary backing ISO 2424	PA, PES
Secondary backing ISO 2424	Action back
Overall weight ISO 8543	approx. 2360 g/m ²
Overall thickness ISO 1765	approx. 4,50 mm
Pile service weight	approx. 750 g/m ²

Application

Wearability EN 1307	commercial use heavy (33)
Comfort class EN 1307	LC1

Ecological characteristics

Conformity certificate	0809-CPR-19006323 - C2
DOP	1060-OC-6323-C2
EPD (Environmental Product Declaration)	EPD-OBJ-20220317-CBC1-EN
Prodis-ID	09A7DCB6

Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4



Release Date 10.4.2026.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com