


OBJECT CARPET

Typical characteristics

| | |
|-------------------------------|--|
| Name of article |  Lotis 900 |
| Method of production ISO 2424 | Tufted |
| Width ISO 3018 | approx. 400 cm |
| Surface structure ISO 2424 | Loop |
| Colourways | Uni |
| Pattern repeat | 2x- |
| Pile material ISO 2424 | 100% PA 6.6 |
| Primary backing ISO 2424 | PES |
| Secondary backing ISO 2424 | Conductive action back |
| Overall weight ISO 8543 | approx. 2300 g/m ² |
| Overall thickness ISO 1765 | approx. 7,5 mm |
| Pile service weight | approx. 930 g/m ² |
| Additional equipment | OC Protect |

Application

| | |
|-----------------------|---------------------------|
| Wearability EN 1307 | commercial use heavy (33) |
| Comfort class EN 1307 | LC3 |

Ecological characteristics

| | |
|---|--------------------------|
| Conformity certificate | 1658-CPR-3033 |
| DOP | 1045-116974 |
| EPD (Environmental Product Declaration) | EPD-GUT-20160118-CCA1-EN |

Fastness

| | |
|----------------------------------|-------|
| Light fastness ISO 105-B02 | ≥ 5 |
| Water fastness EN ISO 105 E01 | ≥ 4 |
| Friction fastness EN ISO 105-X12 | ≥ 3-4 |



Release Date 1.7.2019.

OBJECT CARPET GmbH Rechbergstrasse 19 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com