

OBJECT CARPET

Typical characteristics

Name of article	 Madra 1100
Method of production ISO 2424	Tufted
Width ISO 3018	approx. 400
Surface structure ISO 2424	Cut
Colourways	Uni
Pile material ISO 2424	100% PA 6.6
Primary backing ISO 2424	PES
Secondary backing ISO 2424	Conductive action back
Overall weight ISO 8543	approx. 2500 g/m ²
Overall thickness ISO 1765	approx. 8,0 mm
Pile service weight	approx. 1100 g/m ²

Application

Wearability EN 1307	commercial use heavy (33)
Comfort class EN 1307	LC4

Ecological characteristics

Conformity certificate	1658-CPR-3397
DOP	1060 OC 3379
EPD (Environmental Product Declaration)	EPD-GUT-20160118-CCA1-EN
Prodis-ID	A0F36142

Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4



Release Date 21.4.2024.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com