# OBJECT CARPET

## Typical characteristics

| | |
|---|---|
| Name of article | **AT-Marrakesh** |
| Method of production ISO 2424 | Flat woven |
| Width ISO 3018 | approx. 50x50 |
| Surface structure ISO 2424 | Loop |
| Colourways | Style |
| Pile material ISO 2424 | 100% PET |
| Primary backing ISO 2424 | PET |
| Secondary backing ISO 2424 | Welltex® Acoustic |
| Overall weight ISO 8543 | approx. 3700 g/m$^2$ |
| Overall thickness ISO 1765 | approx. 5,0 mm |
| Pile service weight | approx. 655 g/m$^2$ |

## Application

| | |
|---|---|
| Wearability EN 1307 | commercial use heavy (33) |
| Comfort class EN 1307 | LC1 |

## Ecological characteristics

| | |
|---|---|
| Conformity certificate | 0809-CPR-19006323 - C4 |
| DOP | 1045-123614 |
| EPD (Environmental Product Declaration) | EPD-OBJ-20190010-CBC1-EN |
| Prodis-ID | 9C9535A2 |

## Fastness

| | |
|---|---|
| Light fastness ISO 105-B02 | ≥ 5 |
| Water fastness EN ISO 105 E01 | ≥ 4 |
| Friction fastness EN ISO 105-X12 | ≥ 3-4 |

*Release Date 14.11.2022.*

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com