



Name of article	<b>Neo 1000</b>	Secondary backing ISO 2424	Welltex® Circular Acoustic
Method of production ISO 2424	Tufted	Electrostatic loading ISO 6356	< 2 KV
Width ISO 3018	ca. 400	Surface resistivity ISO 10965 ROT	10 <sup>9</sup> Ω
Surface structure ISO 2424	Loop	Transparency to heat ISO 8302	0,09 K*m <sup>2</sup> /W
Colourways	Mix	Light fastness ISO 105-B02	≥ 6
Pile material ISO 2424	100% PET	Water fastness EN ISO 105 E01	≥ 5
Primary backing ISO 2424	PET (100% Recycelt)	Friction fastness EN ISO 105-X12	≥ 5
Overall weight ISO 8543	ca. 1950 g/m <sup>2</sup>	Stitch rate ISO 1763	ca. 270.400/m <sup>2</sup>
Overall thickness ISO 1765	ca. 8,0 mm		
Pile service weight	ca. 950 g/m <sup>2</sup>		



EN 14041 | DOP: 1045-129450 | NB: 1658

**Health-promoting properties AIR**

- Free from PVC and bitumen.
- Free from latex and fillers.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers



**Health-promoting ACOUSTIC properties**

- High acoustic effectiveness as standard
  - Improved impact sound insulation +27dB
  - Enhanced room acoustics +0.25α<sub>w</sub>
- |                |      |      |      |      |      |      |
|----------------|------|------|------|------|------|------|
| Hz             | 125  | 250  | 500  | 1000 | 2000 | 4000 |
| α <sub>s</sub> | 0,02 | 0,05 | 0,10 | 0,31 | 0,67 | 0,70 |
- Increased employee concentration and motivation through enhanced well-being



**Environmental properties**

7208CC1E  
PRODIS-ID | product pass

- 100% recycling and take-back responsibility by the manufacturer
- Recycled primary backing
- 100% recycled secondary backing
- Easy cleaning with water only



**Product Information**

The mono-material carpet made of 100% polyester has a calm, timeless surface appearance with its highly and deeply structured yarn loops.

**Installation Instructions**

The use of a double seam cut is recommended for the installation of reusable carpeting to ensure a clean transition. If a fixation is used, the product can be easily removed after use, recycled and returned to the production cycle.



Made in Europe (production according to EU standard)