Characteristic features EN 1307



Name of article
Method of production ISO 2424
Width ISO 3018
Surface structure ISO 2424
Colourways
Pile material ISO 2424
Primary backing ISO 2424

Colourways
Pile material ISO 2424
Primary backing ISO 2424
Overall weight ISO 8543
Overall thickness ISO 1765
Pile service weight

Net Web
Flat woven
ca. 400
Schlinge
Mix
100 % Polyamid
PES, PP
ca. 2450 g/m²
ca. 5 mm

Secondary backing ISO 2424 Action back Electrostatic loading ISO 6356 < 2 KV Surface resistivity ISO 10965 ROT Transparency to heat ISO 8302 0,09 K*m²/W Light fastness ISO 105-B02 ≥ 5 Water fastness EN ISO 105 E01 4 Friction fastness EN ISO 105-X12 ≥ 3 -4 Stitch rate ISO 1763 ca. 144000/m²















ca. 800 g/m^2



EN 14041 | DOP: 1060-OC-6323-C2 CPR: 0809-CPR-19006323 - C2 | NB: 1658











- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers



Health-promoting ACOUSTIC properties



- Improved impact sound insulation +16dB Enhanced room acoustics +0.15α_w
- Hz 125 250 500 1000 2000 4000 α_s 0,00 0,00 0,05 0,20 0,15 0,10
- Increased employee concentration and motivation through enhanced well-being
- Acoustically effective





Environmental properties

AACC96BB

- · Recycled primary backing
- Easy cleaning with water only



* * * * * * * * *

Made in Europe (production according to EU standard)

Product Information

The fine weave quality creates a coarsely structured, melange-like surface appearance. Seam markings on small-patterned flatweaves are typical of the fabric. The reason for the occasionally occurring zipper effect in the appearance at the seam edges does not lie in the design, but in the fabric construction or patterning is revealed in its simplicity.

Installation Instructions

The precise seam cut is carried out professionally using a steel ruler and a laying knife with a trapezoidal blade. The use of pile scissors is recommended for processing cut studs to ensure a flawless appearance.

Data status 30.06.2025. Subject to changes due to technical advancements.