


# OBJECT CARPET

## Typical characteristics

Name of article	 <b>Newcon</b>
Method of production ISO 2424	Getuftet
Width ISO 3018	approx. 400
Surface structure ISO 2424	Schlinge
Colourways	Style
Pile material ISO 2424	100 % Polyamid Econyl® by Aquafil
Primary backing ISO 2424	PES
Secondary backing ISO 2424	Conductive action back
Overall weight ISO 8543	approx. 1900 g/m <sup>2</sup>
Overall thickness ISO 1765	approx. 5.8 mm
Pile service weight	approx. 550 g/m <sup>2</sup>

## Application

Wearability EN 1307	commercial use heavy (33)
Comfort class EN 1307	LC1

## Ecological characteristics

Conformity certificate	1658-CPR 3424
DOP	1060 TT 3424
EPD (Environmental Product Declaration)	EPD-GUT-20170016-CCA1-DE

## Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	4
Friction fastness EN ISO 105-X12	≥ 3-4



Release Date 14.11.2022.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf  
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com