OBJECT CARPET

Typical characteristics

Name of article	**Nyltecc 700**
Method of production ISO 2424	Tufted
Width ISO 3018	approx. 400 cm
Surface structure ISO 2424	Cut
Colourways	Mix
Pile material ISO 2424	100% Econyl® by Aquafil
Primary backing ISO 2424	PA, PP
Secondary backing ISO 2424	Conductive action back
Overall weight ISO 8543	approx. 2000 g/m^2
Overall thickness ISO 1765	approx. 6 mm
Pile service weight	approx. 730 g/m^2

Application

Wearability EN 1307	commercial use heavy (33)
Comfort class EN 1307	LC2

Ecological characteristics

Conformity certificate	1658-CPR-3032
DOP	1045-110648
EPD (Environmental Product Declaration)	EPD-GUT-20160117-CCA1-EN

Fastness

Light fastness ISO 105-B02	≥ 6
Water fastness EN ISO 105 E01	≥ 5
Friction fastness EN ISO 105-X12	≥ 5

Release Date 1.7.2019.

OBJECT CARPET GmbH Rechbergstrasse 19 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com