



|                               |                        |                                   |                            |
|-------------------------------|------------------------|-----------------------------------|----------------------------|
| Name of article               | <b>AT Nyltecc 700</b>  | Secondary backing ISO 2424        | Welltex Circular® Acoustic |
| Method of production ISO 2424 | Tufted                 | Electrostatic loading ISO 6356    | < 2 KV                     |
| Width ISO 3018                | ca. 50x50              | Surface resistivity ISO 10965 ROT | 10 <sup>9</sup> Ω          |
| Surface structure ISO 2424    | Cut                    | Transparency to heat ISO 8302     | 0,09 K*m² /W               |
| Colourways                    | Mix                    | Light fastness ISO 105-B02        | ≥ 6                        |
| Pile material ISO 2424        | 100% Econyl by Aquafil | Water fastness EN ISO 105 E01     | ≥ 5                        |
| Primary backing ISO 2424      | PES                    | Friction fastness EN ISO 105-X12  | ≥ 5                        |
| Overall weight ISO 8543       | ca. 2420 g/m²          | Stitch rate ISO 1763              | ca. 165.900/m²             |
| Overall thickness ISO 1765    | ca. 10,1 mm            |                                   |                            |
| Pile service weight           | ca. 710 g/m²           |                                   |                            |



EN 14041 | DOP: 1060-OC-3566  
CPR: 1658-CPR-3566 | NB: 1658

## Health-promoting properties AIR



- Free from PVC and bitumen.
- Free from latex and fillers.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers

70 710 3720-12



## Health-promoting ACOUSTIC properties



- High acoustic effectiveness as standard
- Improved impact sound insulation +32dB
- Enhanced room acoustics +0.3α<sub>w</sub>

| Hz             | 125  | 250  | 500  | 1000 | 2000 | 4000 |
|----------------|------|------|------|------|------|------|
| α <sub>s</sub> | 0,00 | 0,05 | 0,30 | 0,35 | 0,35 | 0,45 |

- Increased employee concentration and motivation through enhanced well-being

HEALTH



## Environmental properties

PRODID-ID | product pass

- Completely recyclable
- 100% recycled yarn
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- Easy cleaning with water only



## Product Information

AT NYLTECC - The carpet presents itself with a velour construction, featuring a shimmering surface of elegant appearance. The choice of color has a decisive impact on the visibility of the tiles as well as the maintenance effort. The lighter the color choice, the more delicate it can be.

## Installation Instructions

Great attention is placed on laying the tiles in a harmonious alignment, thus creating a coherent overall image. At the same time, care is taken not to trap the pile - that is, the yarn ends - at the seams, in order to preserve both the aesthetic quality and the lasting functionality of the carpet.



Made in Europe (production according to EU standard)

Data status 18.04.2026. Subject to changes due to technical advancements.