


OBJECT CARPET

Typical characteristics

Name of article	 Pearl 1300
Method of production ISO 2424	Tufted
Width ISO 3018	approx. 400 cm
Surface structure ISO 2424	Loop
Colourways	Uni
Pile material ISO 2424	100% PA 6.6 Antron®
Primary backing ISO 2424	PA, PP
Secondary backing ISO 2424	Conductive action back
Overall weight ISO 8543	approx. 2500 g/m ²
Overall thickness ISO 1765	approx. 7,0 mm
Pile service weight	approx. 1300 g/m ²
Additional equipment	OC Protect

Application

Wearability EN 1307	commercial use heavy (33)
Comfort class EN 1307	LC4

Ecological characteristics

Conformity certificate	1658-CPR-3033
DOP	1045-115249
EPD (Environmental Product Declaration)	EPD-GUT-20160118-CCA1-EN

Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4



Release Date 1.7.2019.

OBJECT CARPET GmbH Rechbergstrasse 19 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com