#### Characteristic features EN 1307

Name of article

Method of production ISO 2424

Width ISO 3018

Surface structure ISO 2424

Colourways

Pile material ISO 2424

Primary backing ISO 2424

Overall weight ISO 8543

Overall thickness ISO 1765

Pile service weight

AT Poodle 1400

Tufted

ca. 50x50

Shag

Uni

100% PA 6.6

**PES** 

ca.  $3050 \text{ g/m}^2$ 

ca. 11,5 mm

ca.  $1400 \text{ g/m}^2$ 

Secondary backing ISO 2424

Electrostatic loading ISO 6356

Surface resistivity ISO 10965 ROT

Transparency to heat ISO 8302

Light fastness ISO 105-B02

Water fastness EN ISO 105 E01 Friction fastness EN ISO 105-X12

Stitch rate ISO 1763

Welltex® Acoustic

< 2 KV

 $10^9 \Omega$ 

 $0.09 \, K^* m^2 / W$ 

> 5

> 4

> 3-4

ca.  $51.000/m^2$ 



























EN 14041 | DOP: 1060-OC-3497 CPR: 1658-CPR-3497 | NB: 1658















- Free from PVC and bitumen.
- Free from formaldehyde.
- Reduction of fine dust in the breathing air.
- Free from harmful emissions and odors.
- TVOC limits are immediately met.
- Suitable for allergy sufferers



70 710 3720-8





# **Health-promoting ACOUSTIC properties**



- High acoustic effectiveness as standard
- Improved impact sound insulation +31dB Enhanced room acoustics  $+0.4\alpha$
- 1000 Hz 125 250 500 2000 4000 0,10 0,40 0,50 0,05 0,50 0,65
- Increased employee concentration and motivation through enhanced well-being

## **Environmental properties**

98547C8F

- Completely recyclable
- Recycled primary backing
- 100% recycled secondary backing
- Weight reduction of up to 50%
- · Easy cleaning with water only

















Made in Europe (production according to EU standard)

### **Product Information**

AT POODLE - The carpet presents itself with a velour construction, featuring a shimmering surface of elegant appearance. The choice of color has a decisive impact on the visibility of the tiles as well as the maintenance effort. The lighter the color choice, the more delicate it can be.

## **Installation Instructions**

Great attention is placed on laying the tiles in a harmonious alignment, thus creating a coherent overall image. At the same time, care is taken not to trap the pile - that is, the yarn ends at the seams, in order to preserve both the aesthetic quality and the lasting functionality of the carpet.

