

OBJECT CARPET

Typical characteristics

Name of article	 AT-Reykjavik
Method of production ISO 2424	Flat woven
Width ISO 3018	approx. 50x50
Surface structure ISO 2424	Loop
Colourways	Style
Pile material ISO 2424	100% PET
Primary backing ISO 2424	PET
Secondary backing ISO 2424	Welltex® Acoustic
Overall weight ISO 8543	approx. 3700 g/m ²
Overall thickness ISO 1765	approx. 5,0 mm
Pile service weight	approx. 655 g/m ²

Application

Wearability EN 1307	commercial use heavy (33)
Comfort class EN 1307	LC1

Ecological characteristics

Conformity certificate	0809-CPR-19006323 - C4
DOP	1045-123614
EPD (Environmental Product Declaration)	EPD-OBJ-20190010-CBC1-EN
Prodis-ID	9C9535A2

Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4



Release Date 14.11.2022.

OBJECT CARPET GmbH Marie-Curie-Strasse 3 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com